


# Sherlog

# HATCHecker

## WHEN HATCH COVER TIGHTNESS MATTERS



**Dual Measure Mode.**  
Switch between static and live streaming with a single button push.

### Focused

Hatch cover leakage and wetting damage to cargo are a persistent problem in the marine industry. Confirm that hatch covers are weathertight and compliant with ruling regulations by using the new Sherlog HATCHecker which includes cutting edge technology that makes both the T9 transmitter and handheld receiver light, compact, robust and suitable for use in the harsh marine environment.

### Simple

The ergonomic and revolutionary design, vibrant colour display and limited number of keys make the Sherlog HATCHecker easy to use, handy for travellers and allows for reliable leak detection with pinpoint accuracy on board ships.

### Affordable

SDT's renowned quality and engineering, together with pioneering design and competitive price setting make the Sherlog HATCHecker the most suitable and affordable solution for testing hatch cover tightness.

Remote controlled and powerful transmitter, suitable for testing any hold or space.



## T-SONIC9



Ultrasound  
Solutions

[sdtultrasound.com](http://sdtultrasound.com)

# Sherlog HATCHecker features

## Description

The Sherlog HATCHecker is an ultrasound solution designed for testing hatch cover tightness. Use the Sherlog HATCHecker to find leaky areas on the hatch covers with pinpoint accuracy. The Sherlog HATCHecker works with SDT's ergonomic Flexible Sensor and the T-Sonic9 transmitter.

## Kit Contents

- Sherlog HATCHecker (receiver)
- T-Sonic9 (transmitter)
- + Remote control
- Shoulder strap
- FlexID2 Sensor (10mm)
- Handle (400mm)
- Sensor cable
- USB Cable
- Headphones
- Screwdriver (toolkit)
- 8 AA Batteries
- Carrying case
- Manual



### Sherlog HATCHecker Kit Specifications

General	
Function	Ultrasound measurement device
Operable with	SDT FLEX ID2 & T-Sonic9
Measurement interface	1 channel via a 7 pole LEMO connector
Display	160x128 pixels Color OLED
Keyboard	5 function keys
Typical measurement range	-10 to 99.9 dBμV (reference 0 dB = 1 μV)
Resolution	0.1 digits
Measurement bandwidth	39.6 to 40.1 kHz
Signal amplification	+30 dB to +102 dB by step of 6 dB
RMS period time	250 milliseconds (main screen)
Sampling frequency	64 kHz/ksps
ADC Resolution	12 bits
Environmental	
Operating temperature range	-10 to +50 °C   14 to 122°F
IP rating	IP42
EMC approvals	EN 61326-1:2013, EN 55011:2016 + A1:2017, EN 61000-4-2:2009, EN 61000-4-3:2006 + A1:2008 + IS1:2009 + A2:2010
Mechanical	
Housing material	ABS
Dimensions housing	158x59x38.5 mm   6.22"x2.32"x1.51"
Weight	164g   5.78oz
Battery/Utility connector	USB Mini-B 5-pin
Power	
Battery	2 AA size batteries
Autonomy	7 hours
Audio	
Operable with	SDT provided head set only
Headset	25dB NRR Peltor HQ headset

### T-Sonic9 Specifications

General													
Transmitter frequencies	39.9 and 40.1 kHz												
Wobulation period	80 ms												
Bluetooth range	20m/65ft												
Transmitted Sound Pressure Level at 1m, Ref. 0 dB=0.0002 μbar	<table><tr><td>Level 1</td><td>86 dB SPL</td></tr><tr><td>Level 2</td><td>95 dB SPL</td></tr><tr><td>Level 3</td><td>101 dB SPL</td></tr><tr><td>Level 4</td><td>105 dB SPL</td></tr><tr><td>Level 5</td><td>111 dB SPL</td></tr><tr><td>Level 6</td><td>117 dB SPL</td></tr></table>	Level 1	86 dB SPL	Level 2	95 dB SPL	Level 3	101 dB SPL	Level 4	105 dB SPL	Level 5	111 dB SPL	Level 6	117 dB SPL
Level 1	86 dB SPL												
Level 2	95 dB SPL												
Level 3	101 dB SPL												
Level 4	105 dB SPL												
Level 5	111 dB SPL												
Level 6	117 dB SPL												
Power supply	6 AA batteries or USB Power Supply 5VDC @ 1A												
Battery lifespan With Alkaline Batteries AA LR6	<table><tr><td>Level 1</td><td>24 h</td></tr><tr><td>Level 2</td><td>21 h</td></tr><tr><td>Level 3</td><td>19 h</td></tr><tr><td>Level 4</td><td>18:30 h</td></tr><tr><td>Level 5</td><td>11 h</td></tr><tr><td>Level 6</td><td>5:30 h</td></tr></table>	Level 1	24 h	Level 2	21 h	Level 3	19 h	Level 4	18:30 h	Level 5	11 h	Level 6	5:30 h
Level 1	24 h												
Level 2	21 h												
Level 3	19 h												
Level 4	18:30 h												
Level 5	11 h												
Level 6	5:30 h												
Environmental													
Operating temperature range	-10 to +50°C 14 to 122°F Non-condensing												
IP rating	40												
Mechanical													
Housing material	ABS / PC												
Weight (w/ batteries)	400g(14oz)												
Wireless Communication													
Type	Bluetooth® 4.0 Certified ISM 2.4GHz module.												
Frequency band	2402 – 2480 MHz												
Transmitter power max.	4dBm												
Using distance	20m/65ft												

### FlexID2 Sensor Specifications

General	
Sensor type	Airborne removable resonance sensor Ø 10mm
Resonant frequency	40.0±1.0 KHz
Bandwidth	2.5 kHz at -6dB
Sensitivity with removable sensor Ø 10mm	-42dB (at 40.0KHz; 0dB = 1 volt/μbar)
Length	545 mm / 21.8 in 847 mm / 32.2 in with Extension Tube
Weight	336 grams / 11.8 oz 466 grams / 16.4 oz with Extension Tube 604 grams / 21.3 oz with Telescopic Pool Handle
Operating Temperature	-30 to 70°C / -22 to 158°F Non-condensing
Connector	Lemo 7 poles



## SHERLOGReporter

Use the SDT SHERLOGReporter App to quickly create comprehensive hatch cover test reports and share them with principals in real time.



### SDT: leader in acoustic detection for industrial and marine maintenance

SDT provides ultrasound solutions that help our customers gain a better understanding about the health of their assets. We help them predict failures, control tightness, optimize energy costs, and improve product quality while contributing to the overall reliability of their assets.



## Ultrasound Solutions

### SDT International s.a./n.v.

Boulevard de l'Humanité 415  
B-1190 Brussels  
Belgium  
Tél: +32(0)2-332 32 25  
Email: info@sdtultrasound.com

### SDT North America

7677 County Road 2, Cobourg, ON  
K9A 0X4 Canada  
Toll Free NA: 1-800-667-5325  
Intl Phone: 1-905-377-1313  
Email: hearmore@sdtultrasound.com

Your SDT Certified Partner:  
Precise Reliability Services, Inc.  
75 Clairadan Dr, Suite A  
Powell, OH 43065  
614-376-4078  
www.precisereliability.com  
info@precisereliability.com